

October 29, 2018

Caliber Collision Centers
401 E. Corporate Drive, Suite 150
Lewisville, TX 75057

RE: Hazardous Material Storage

To Whom It May Concern,

The following details the hazardous material storage and disposal procedures for Caliber Collision Centers:

1. **Solvent-Based Paint** - Class 1C Flammable - 33 gallons - These materials are packaged in closed metal containers that range in size from pint to 5-gallon. All containers are stored in a mix room with explosion proof fixtures, mechanical ventilation, and secondary spill containment. Any material waste is stored in a 55-gallon closed metal drum inside secondary spill containment until it is transported and disposed by a licensed waste hauler.
2. **Water-Based Paint** - Class IIIA Combustible - 22 gallons - These materials are packaged in closed metal containers that range in size from pint to 1-gallon. All containers are stored in a mix room with explosion proof fixtures, mechanical ventilation, and secondary spill containment. Any material waste is stored in a 55-gallon closed plastic drum inside secondary spill containment until it is transported and disposed by a licensed waste hauler.
3. **Lacquer Thinner** - Class 1B Flammable - 35 gallons - This material is packaged in a closed metal 30-gallon drum and used as a cleaning solvent. The drum is stored in the mix room with explosion proof fixtures, mechanical ventilation, and secondary spill containment. Any material waste is stored in a 55-gallon closed metal drum inside secondary spill containment until it is transported and disposed by a licensed waste hauler.
4. **Antifreeze** - Class IIIB Combustible - 5 gallons - This material is packaged in plastic containers that range in size from quart to 1-gallon. Any material waste is stored in a 55-gallon closed metal drum inside secondary spill containment until it is transported and disposed by a licensed waste hauler.
5. **Motor Oil** - Class IIIB Combustible - 5 gallons - This material is packaged in quart size plastic containers and is stored in the body department removed from any floor drains. Any material waste is stored in a 55-gallon closed metal drum inside secondary spill containment until it is transported and disposed by a licensed waste hauler.
6. **Acetylene** - Flammable Gas Cylinder - 250 cubic feet - This material is packaged in a compressed gas cylinder and is stored in the body department removed from any ignition or oxidizing sources. Cylinders are stored upright, capped, and securely chained to a wall to prevent tipping. These materials are fully consumed and do not generate any waste.

October 29, 2018

7. **Oxygen** - Oxidizing Gas Cylinder - 250 cubic feet - This material is packaged in a compressed gas cylinder and is stored in the body department removed from any ignition sources. Cylinders are stored upright, capped, and securely chained to a wall to prevent tipping. These materials are fully consumed and do not generate any waste.
8. **Argon-Carbon Dioxide** - Non-Flammable Gas Cylinder - 400 cubic feet - This material is packaged in a compressed gas cylinder and is stored in the body department removed from any ignition sources. Cylinders are stored upright, capped, and securely chained to a wall to prevent tipping. These materials are fully consumed and do not generate any waste.
9. **Nitrogen** - Non-Flammable Gas Cylinder - 125 cubic feet - This material is packaged in a compressed gas cylinder and is stored in the body department removed from any ignition sources. Cylinders are stored upright, capped, and securely chained to a wall to prevent tipping. These materials are fully consumed and do not generate any waste.

If you have any questions, please do not hesitate to contact us.

Sincerely,

Brandon C. Thomas

Brandon Thomas
President
GMG EnviroSafe, Inc.
Office: 800-619-9733
Cell: 815-671-1005
Email: BThomas@GMGEnviroSafe.com